
Introducing the Cast for Social Computing: Life-like Characters

Helmut Prendinger and Mitsuru Ishizuka

Department of Information and Communication Engineering
Graduate School of Information Science and Technology
University of Tokyo
7-3-1 Hongo, Bunkyo-ku, Tokyo 113-8656, Japan
prendinger@acm.org, ishizuka@miv.t.u-tokyo.ac.jp

Summary. Life-like characters are one of the most exciting technologies for human-computer interface applications. They convincingly take the roles of virtual presenters, synthetic actors and sales personas, teammates and tutors. A common characteristic underlying their believability or life-likeness as conversational partners are computational models that provide them with affective functions such as synthetic emotions and personalities, and implement human interactive behavior or presentation skills. In *Social Computing*, a paradigm that aims to support the tendency of humans to interact with computers as social actors, life-like characters are key. They may embody the interface between humans and computers, and thus improve the otherwise poor communicative capabilities of computational devices.

The success of life-like character applications today heavily relies on the careful crafting of their designers, mostly programmers. The wide dissemination of life-like character technology in interactive systems, however, will greatly depend on the availability of tools that facilitate scripting of intelligent life-like behavior. The core tasks include the synchronization of synthetic speech and gestures, the expression of emotion and personality by means of body movement and facial display, the coordination of the embodied conversational behavior of multiple characters possibly including the user, and the design of artificial minds for synthetic characters.

In this chapter we will first describe what life-like characters are, and how they differ from related synthetic entities. We will then explain how life-like character technologies may change and improve the interaction between humans and computers. Next, we report on some of the most promising character scripting and representation languages as well as authoring tools currently available. After that, the most successful life-like character systems are briefly introduced, demonstrating the wide range of applications where embodied agents are at work. Some final remarks on this highly active research field conclude this introductory chapter.

1 Introduction

Life-like characters are synthetic agents apparently living on the screens of computers. An early characterization of life-like characters can be found in the work of Joseph Bates who refers to them as *emotional* [5] and *believable* [6] agents. Bates explains the notion of a “believable character” as “[...] one that provides the illusion of life, and thus permits the audience’s suspension of disbelief.” [6, p. 122]. Following the vision of designing creatures that computer users are willing to perceive as believable or life-like, researchers use a variety of different terms: anthropomorphic agents, avatars, creatures, synthetic actors, non-player characters, and embodied conversational agents [60, 22, 28]. While creation of most terms is inspired by specific character applications, such as avatars for distributed virtual environments like chat systems or non-player characters for interactive games, some terms intend to draw attention to a particular aspect of life-like characters. Embodied conversational agents, for instance, are characters that visually incorporate, or embody, knowledge about the conversational process (Cassell [13]).

To restrict the focus of our discussion, we will draw a line between life-like characters that are graphically represented, or animated, and robotic agents that are realized as physical entities to operate in the physical world (Breazeal-Ferrell and Velásquez [9]). The concept of “life-likeness” is certainly not restricted to animated agents. Dautenhahn [18], for instance, extensively discusses life-likeness in the context of robotic agents. A more subtle distinction concerns the restriction to *animated* rather than *animate* characters. According to Hayes-Roth and Doyle [28], animate characters share all the features of life-like characters except for their embodiment, that is, animate characters are not necessarily animated, but can still be perceived as perfectly life-like.

Although life-likeness is often associated with a ‘life-like’ appearance, animate characters highlight the importance of synthetic minds that give characters individual personality and emotions. Bates [6] draws on the experience of professional character animators [59] when he argues that the portrayal of emotions plays a key role in the aim to create believable characters. On a par with emotions, personality is key to achieve life-likeness. Trappl and Petta [60] dedicated an entire volume to illustrate the personality concept in synthetic character research. Emotion and personality are often seen as the affective bases of believability [43], and sometimes the broader term *social* (or “socially intelligent”) is used to characterize life-likeness [22].

Characters can be life-like in a ‘human-like’ or an ‘animal-like’ way. While the design of human-like characters attracted the majority of researchers, there are also investigations on animal-like characters, especially dogs (Blumberg [8]). An ongoing debate concerns the issue whether the ‘life-likeness’ of characters is more effectively achieved by *realistic* or *cartoon-style* agents. Research that aims to create virtual humans typically follows the realistic approach [14, 24], Thalmann et al. [58] even strive for photorealism. On the other hand, most characters developed in the context of entertainment and

‘infotainment’ systems adhere to the approach that uses cartoon-style characters [2, 47, 23, 62]. While the design of realistic characters is a high research aim *per se*, they do not necessarily outperform cartoon-style characters in the perception of the user. As opposed to cartoon-style characters, users put high expectations in the performance of realistic looking characters, which bears the risk that even small behavior deficiencies lead to user irritation and dissatisfaction. The question of realistic vs. cartoon-style agents can eventually only be decided empirically with respect to specific application scenarios. McBreen et al. [39], for instance, investigate effectiveness and user acceptability of different types of synthetic agents. A related empirical question concerns the benefits of displaying characters as facial agents (‘talking heads’), full-body or ‘upper-body plus face’ agents.

2 Towards Social Computing

Since human-human communication is a highly effective and efficient way of interaction, life-like characters are promising candidates to improve human-computer interaction (HCI). Embodied agents may use multiple modalities such as voice, gestures and facial expression to convey information and regulate communication. The work of Reeves and Nass [50] shows that humans are (already) strongly biased to interpret synthetic entities as social actors if they display some human-like features – the Media Equation. The authors carried out a series of classical psychological tests of human-human social interaction, but replaced one interlocutor by a computer with human-sounding voice and a particular role such as companion or opponent. The results of those experiments suggest that humans treat computers in an essentially natural way – as social actors – with a tendency, for instance, to be nicer in ‘face-to-face’ interactions than in third party conversations. More support for this result is provided by Lester et al. [33] who investigated the impact of animated agents in educational software along the dimensions of motivation and helpfulness, and coined the term ‘persona effect’ “[...] which is that the presence of a life-like character in an interactive learning environment – even one that is not expressive – can have a strong positive effect on student’s perception of their learning experience.” [33, p. 359].

There are hence strong arguments to make the interface *social* by adding life-like characters that have the means to send social cues to the user and possibly even receive such signals. However, it should not be concluded that *all* interfaces can be improved by making them social. As an approximation, it can be said that character-based interfaces are beneficial whenever the interaction task involves social activity. Training, presentation, and sales certainly fall under this category. By contrast, there are computer related activities that typically do not require social interaction. Building a spreadsheet, for instance, is a mechanical task and most users would not want to have a colleague watching or interrupting them [21]. The same may hold true for the

presence of a synthetic agent. On the other hand, social encounters also include information exchange between people that share similar interests, where life-like characters may act as match-makers at public meeting places. In order to support ‘community awareness’, Sumi and Mase [55] investigated this form of computer-mediated communication.

As a HCI paradigm, the goal of character-based human-computer interfaces seems to be diametrically opposed to that of the ‘disappearing computer’ concept in ubiquitous and invisible computing (Weiser [61]). Those technologies are intended to “weave themselves into the fabric of everyday life until they are indistinguishable from it.” [61, p. 94]. By contrast, the power of character-based HCI derives from the fact that people *know* how to interact with other people by using the modalities of their body (voice, gesture, gaze, etc.) and interpret the bodily signals of their interlocutors. Hence, character-based interfaces aim at realizing embodied interaction and intelligence (Cassell [13]) rather than interaction with ‘invisible’ devices (see also the Gestalt user interface concept of Mariott and Beard [35]).

The vision of *Social Computing* is to achieve natural and effective interaction between humans and computational devices. As argued above, we believe that by employing life-like characters, social computing can be realized most efficiently. Social Computing can be characterized as

- computing that intentionally displays social and affective cues to users and aims to trigger social reactions in users; and
- computing that recognizes affective user states and gives affective feedback to users.

In this paradigm, life-like characters are seen as social actors, and hence as genuine interactive partners for a wide variety of applications, ranging from advisors and sales persona to virtual playfellows. A recent study in the Social Computing paradigm are the ‘relational agents’ described by Bickmore [7], where characters are in the role of assistants for health behavior change (exercise adoption). He characterizes *relational agents* as computational (typically anthropomorphic) artifacts “[...] intended to produce relational cues or otherwise produce a relational response in their users, such as increased liking for or trust in the agent.” [7, p. 27].

Besides displaying social cues, the second key premise for Social Computing is that life-like characters recognize social cues of their interlocutor, such as the affective state of the user. In this respect, Social Computing shares the motivation and goal of Affective Computing (Picard [46]). In the context of a tele-home care application, Lisetti et al. [34] take physiological signals of the user so that a life-like character may respond appropriately. Conati [17] suggests an animated agent that adapt its behavior according to assessed user emotions in the setting of an educational game. Mori et al. [41] conducted an experiment that utilizes biosignals of users to demonstrate the calming effect of emphatic character behavior.

The related notion of ‘Social Intelligence Design’ (Nishida [42]), on the other hand, emphasizes the role of the web infrastructure as a means of computer-mediated interaction, community building and evolution, and collective intelligence, rather than (social) human-agent interaction.

3 Authoring Life-like Characters

One of the most challenging tasks in life-like character research is the design of powerful and flexible authoring tools for content experts. Unlike animators, who are skillful in creating believable synthetic characters, non-professionals will need appropriate scripting tools to build character-based applications (see also Rist [51]). Animating the visual appearance of life-like characters and integrating them into an application environment involves a large number of complex and highly inter-related tasks, such as

- The synchronization of synthetic speech, gaze, and gestures.
- The expression of personality and affective state by means of body movement, facial display, and speech.
- The coordination of the bodily behavior of multiple characters, including the synchronization of the characters’ conversational behavior (for instance, turn-taking).
- The communication between one or more characters and the user.

Observe that the mentioned tasks already assume that characters can be controlled at a rather ‘high’ level, where designers may abstract from low-level concerns such as changing each individual degree of freedom in the character’s motion model. The Character Markup Language (CML) contains both medium-low level tags to define the gesture behavior of a character as well as high level tags that define combinations of other tagging structures (Arafa et al. [3]). Furthermore, CML allows to define high level attributes to modulate a character’s behavior according to its emotional state and personality. The Virtual Human Markup Language (VHML) provides high and low level tagging structures for facial and bodily animation, gesture, speech, emotion, as well as dialogue management (Mariott and Stallo [36]). The Scripting Technology for Embodied Persona (STEP) language contains high level control specifications for scripting communicative gestures of 3D animated agents (Huang et al. [29]). Being based on dynamic logic [25], the STEP language includes constructs known from programming languages, such as sequential and non-deterministic execution of behaviors or actions, (non-deterministic) iteration of behaviors, and behaviors that are executed if certain conditions are met.

The human interpretation process is very sensitive to and easily disturbed by a character’s ‘inconsistent’ or ‘unnatural’ behavior, whatever type of ‘nature’ (realistic or not) is applicable. The challenge here is to maintain consistency between an agent’s internal emotional state and various forms of associated outward behavior such as speech and body movements (Gratch

et al. [24]). An agent that speaks with a cheerful voice without co-occurring happy facial expression will seem awkward or even fake. Another challenge is to keep consistency of agents over time, allowing for changes in their response tendencies as a result of the interaction history with other agents (Prendinger and Ishizuka [48], Bickmore [7]).

Allbeck and Badler [1] developed an extensive framework for representing embodied characters and objects in virtual environments, called Parameterized Action Representation (PAR). This representation allows to specify a large number of action parameters to control character behavior, including applicability conditions, purpose, duration, manner, and many more. Most notably, character actions can be modulated by specifying affect related parameters, emotion and personality. In order to achieve a high level of naturalness in expressive behaviors, the authors developed the EMOTE system which is based on movement observation science. With respect to conversational behavior, Cassell et al. [16] propose the BEAT (Behavior Expression Animation Toolkit) system as an elaborate mechanism to support consistency and accurate synchronization between a character's speech and conversational gestures. The BEAT system uses a pipelined approach where the Text-to-Speech (TTS) engine produces a fixed timeline which constrains subsequently added gestures. The meaning of the input text is first analyzed semantically and then appropriate gestures are selected to co-occur with the spoken text.

Most approaches to scripting virtual environments focus on designing the characters themselves and interactions between characters and virtual objects, with rudimentary consideration of the representation of interactions among characters and the user. The motivation for the Affective Presentation Markup Language (APML) developed by De Carolis et al. [11] are communicative functions, which makes the language similar to the BEAT system [16]. In addition to turn-taking behavior, APML includes the speaker's belief state (certainty of utterance) and intention (request, inform). The work of Mateas and Stern [38] widens the spectrum of character scripting to interactive scenario scripting to also include another agent and a human user. The authors propose ABL (A Behavior Language), a language that allows to author believable characters for interactive drama. Unlike most other scripting approaches, which are XML-based [16, 11], ABL is a reactive planning language with character behaviors written in a Java-style syntax. Most notably, ABL that may encode 'joint plans' that describe the coordinated behavior of characters as one entity rather than having autonomous characters work out a joint plan (which would require complex reasoning, message passing, and so forth). However, joint plans are still reactive, letting the user to interfere with plan execution during interaction.

The next step in providing support for creating life-like character applications for non-specialists are character toolkits that address the needs of content providers. The Multi-modal Presentation Markup Language (MPML), for instance, offers a visual editor that allows to script interactive multi-character presentations in a drag-and-drop fashion using a graphical representation of

the presentation flow (Prendinger et al. [49]). MPML also provides an interface to the Scripting Emotion-based Agent Minds (SCREAM) system that enables authors to specify the propositional attitudes and affect related processes of a character's (synthetic) brain [49]. While MPML uses the Microsoft Agent package to control animated characters [40], the Galatea software toolkit allows authors to personalize core features of a facial spoken dialogue agent (Kawamoto et al. [31]). Galatea consists of interfaced modules that are all modifiable: speech synthesizer, speech recognizer, facial animation synthesizer, and task dialogue manager. As described above, the BEAT system is a toolkit to synchronize automatically analyzed speech with nonverbal behaviors (Cassell et al. [16]). The toolkit is extensible, and new rules encoding linguistic and contextual analysis of textual input are easily added.

Another challenge for character-based applications is to adequately account for the user's behavior, in particular, the user's affective state (Picard [46]). Marking up user input modalities rather than character (output) modalities is a hitherto entirely unexplored application of scripting technology. Marriott and Beard [35] propose a 'complete user interaction' paradigm which they call *Gestalt User Interface* "an interface that should be reactive to, and proactive of, the perceived desires of the user through emotion and gesture". User interaction modalities such as speech, facial expressions and body gestures are analyzed and then transformed to an XML structure that can be 'played back' by a VHML-based talking head or provide the conditions to decide on the desired character response.

4 Life-like Character Applications and Systems

Recent years have witnessed a considerable and growing interest in employing life-like characters for tasks that are typically performed by humans. In the following, we list some of the more prominent deployed character applications as well as systems in progress. Issues of designing life-like characters and lessons learned can be found in Hayes-Roth [27] and Petta [45].

Life-like characters are used

- as (virtual) *tutors* and *trainers* in interactive learning environments (de Rosis et al. [20], Johnson et al. [30], Hayes-Roth [26], Conati [17], Marsella et al. [37], Tanaka et al. [57]),
- as *presenters* and *sales persona* on the web and at information booths (Cassell [12], Badler et al. [4], Prendinger et al. [49], Rist et al. [52]),
- as *actors* for entertainment (Rousseau and Hayes-Roth [53], Burke [10], Paiva et al. [44]),
- as *communication partners* in therapy (de Rosis [19], Lisetti et al. [34], Marsella et al. [37]),
- as *personal representatives* in online communities and guidance systems (Cassell et al. [15], Takahashi et al. [56], Sumi [54]), and

- as *information experts* enhancing conventional web search engines (Kitamura [32]).

One of the most successful application fields of life-like character technology are computer-based *learning environments* where embodied agents can perform in a variety of student related roles, especially as tutors and trainers [20, 30, 26, 17, 37, 57]. Marsella et al. [37] describe a Mission Rehearsal Exercise (MRE) system for training peacekeeping missions where a realistic virtual human acts as a sergeant in the role of a mentor or as a soldier in the role of a teammate. In order to support highly believable, responsive, and easily interpretable behavior, the authors base their characters on an architecture for task-oriented behavior (STEVE), and rich models of (social) plan-based emotion processing (Émile), and emotion appraisal and coping behaviors (Carmen’s Bright IDEAS). The MRE system is currently one of the most impressive applications of life-like character technology.

Another application field where life-like characters showed significant progress is character-based *presentation*, especially online sales [12, 4, 49, 52]. Starting with the PPP Persona, Rist et al. [52] developed a series of increasingly powerful character technologies for a wide variety of agent-agent and human-agent interaction scenarios, such as the AiA travel agent, the eShowroom, a RoboCup commentator system (Gerd & Matze), a negotiation dialogue manager (Avatar Arena), the MIAU platform for interactive car sales, and the interactive CrossTalk installation featuring two presentation screens. The work on life-like characters done at DFKI [52] can be seen as the strongest and most covering in the field. While being well motivated and based on psychological and socio-psychological research, it offers powerful technologies for every imaginable interaction mode with and among life-like characters. As previously mentioned, Prendinger et al. [49] developed two scripting tools that focus on creating interactive presentations (MPML) and affect-driven characters (SCREAM), respectively. Both technologies are designed for web-based applications that require multiple character interactions including communication with the user. The implementation of an interactive casino scenario demonstrates the power and flexibility of this approach.

One of the most attractive application fields of life-like characters is the *entertainment* sector where characters perform as virtual actors [53, 10, 38, 44]. Paiva et al. [44] provide a useful classification of character control technologies for story and game applications, based on the autonomy dimension. Besides character related autonomy – (partially) scripted, directed, role constrained, and autonomous – the authors also propose a classification of a user’s control over characters, that is, puppet-like control, guidance, influence, and god-like control. The suggested classification is exemplified by a series of installations: Tristão and Isolda, Papous, Teatrix, FantasyA, and SenToy. Burke [10] describes a powerful architecture that meets the demands of life-like characters for entertainment systems. In particular, he proposes a prediction-based approach that allows for new types of learning and adaptive characters. The

previously mentioned work of Mateas and Stern [38] implements an interactive drama – *Faade* – a real-time 3D interactive drama that demonstrates the capabilities and promise of characters in entertainment systems.

Life-like characters will also play a major role as communication partners in *therapeutic* and *medical* applications [19, 34, 37]. For instance, Marsella et al. [37] propose a system called “Carmen’s Bright IDEAS” (CBI) where users are immersed into a story that features an animated clinical counsellor and another agent that receives help and is designed to have problems similar to the user who interacts with the CBI system. The user may influence the development of the counselling session by selecting interface objects (‘Thought Balloons’) that match her or his current feeling most closely.

The great popularity of internet-based and computer-mediated communications raises the demand for life-like characters that function as personal representatives of users in *online communities* (for instance, chat systems) and *guidance systems* [15, 56, 54]. Sumi [54] developed the AgentSalon system where a visitor of an exhibition is equipped with a PalmGuide that hosts his or her personal agent which may migrate to a big display – then being visible as an embodied character – and start conversing with personal agents of other visitors. Since the agent stores a user’s personal interest profile, the conversation between the personal representatives can reveal shared interests and trigger a conversation between visitors.

A common and one of the most important activities on the web is the *retrieval* of relevant information. Life-like characters have recently also been successfully employed to add value to search engines. Kitamura [32] describes the Multiple Character Interface (MCI) system that aims at assisting users in the information retrieval task. Two MCI-based prototype systems are a co-operative multi-agent system for information retrieval (Venus and Mars) and a competitive multi-agent system for information recommendation (Recommendation Battlers) [32].

The following system can be viewed as a feasibility study on the next generation of natural language understanding systems, including entertainment and helper robots, tutoring and virtual space navigation systems. Tanaka et al. [57] developed a system called “Kirai” which allows to direct virtual characters in a 3D environment. Most notably, the system incorporates a natural language recognition and understanding (NLU) component so that characters can be instructed to perform actions in virtual space via speech input. Speech analysis includes syntactic and semantic analysis, anaphora resolution, ellipsis handling, and a simple mechanism to eliminate the vagueness problem of natural language.

5 Concluding Remarks

In this introductory chapter, the state-of-the-art of life-like character scripting languages and applications has been briefly reviewed. While the future

of embodied characters remains to be seen, the extensive research on character representation languages and scripting tools certainly indicates a growing demand for embodiments of the human-computer interfaces. The most convincing evidence for the continued interest is the large number of deployed and upcoming character applications in a wide variety of applications, from learning and entertainment to online sales and medical advice.

Life-like character research lays the foundations of the Social Computing paradigm, where computers deliberately display social cues and trigger social reactions in users. In order to pass as genuine social actors, life-like characters will eventually also have to be equipped with means to recognize social and affective cues of users, a research topic which we hope to address in a future publication. Although we focussed on animated characters here, many of the gained insights can be transferred to the physical siblings of animated characters, robotic agents. Animated or robotic, the success of those agents will ultimately depend on whether they are – life-like.

Acknowledgments

This research was supported by the Research Grant (1999–2003) for the Future Program (“Mirai Kaitaku”) from the Japanese Society for the Promotion of Science (JSPS).

References

1. Allbeck, J., Badler, N.: Representing and parameterizing agent behaviors. In: *Life-like Characters. Tools, Affective Functions and Applications*, ed. by Prendinger, H., Ishizuka, M. (Springer 2003). This volume.
2. André, E., Rist, T., van Mulken, S., Klesen, M., Baldes, S.: The automated design of believable dialogue for animated presentation teams. In: *Embodied Conversational Agents*, ed. by Cassell, J., Sullivan, J., Prevost, S., Churchill, E. (The MIT Press, Cambridge, MA 2000), pp. 220–255
3. Arafa, Y., Kamyab, K., Mamdani, E.: Towards a unified scripting language. Lessons learned from developing CML & AML. In: *Life-like Characters. Tools, Affective Functions and Applications*, ed. by Prendinger, H., Ishizuka, M. (Springer 2003). This volume.
4. Badler, N.I., Bindiganavale, R., Allbeck, J., Schuler, W., Zhao, L., Palmer, M.: Parameterized action representation for virtual human agents. In: *Embodied Conversational Agents*, ed. by Cassell, J., Sullivan, J., Prevost, S., Churchill, E. (The MIT Press, Cambridge, MA 2000), pp. 256–284
5. Bates, J.: Virtual reality, art, and entertainment. *PRESENCE: Teleoperators and Virtual Environments*, 1(1):133–138 (1992)
6. Bates, J.: The role of emotion in believable agents. *Communications of the ACM*, 37(7):122–125 (1994)
7. Bickmore, T.: *Relational Agents: Effecting Change through Human-Computer Relationships*. PhD thesis (Massachusetts Institute of Technology 2003)

8. Blumberg, B.M.: *Old Tricks, New Dogs: Ethology and Interactive Creatures*. PhD thesis (Massachusetts Institute of Technology 1996)
9. Breazeal-Ferrell, C., Velásquez, J.: Toward teaching a robot "infant" using emotive communication acts. In *Proceedings of Workshop on Socially Situated Intelligence, in conjunction with SAB-98* (1998)
10. Burke, R.: Great expectations :: Prediction in entertainment systems. In: *Life-like Characters. Tools, Affective Functions and Applications*, ed. by Prendinger, H., Ishizuka, M. (Springer 2003). This volume.
11. Carolis, B. De, Pelauchaud, C.: APM: Mark-up language for communicative character expressions. In: *Life-like Characters. Tools, Affective Functions and Applications*, ed. by Prendinger, H., Ishizuka, M. (Springer 2003). This volume.
12. Cassell, J.: More than just another pretty face: Embodied conversational interface agents. *Communications of the ACM*, 43(4):70–78 (2000)
13. Cassell, J.: Embodied conversational agents: Representation and intelligence in user interface. *AI Magazine*, 22(3):67–83 (2001)
14. Cassell, J., Bickmore, T., Campbell, L., Vilhjálmsón, H., Yan, H.: Human conversation as a system framework: Designing embodied conversational agents. In: *Embodied Conversational Agents*, ed. by Cassell, J., Sullivan, J., Prevost, S., Churchill, E. (The MIT Press, Cambridge, MA 2000), pp. 29–63
15. Cassell, J., Vilhjálmsón, H.: Fully embodied conversational avatars: Making communicative behaviors autonomous. *Autonomous Agents and Multi-Agent Systems*, 2:45–64 (1999)
16. Cassell, J., Vilhjálmsón, H., Bickmore, T.: BEAT: the Behavior Expression Animation Toolkit. In: *Life-like Characters. Tools, Affective Functions and Applications*, ed. by Prendinger, H., Ishizuka, M. (Springer 2003). This volume.
17. Conati, C.: Probabilistic assessment of user's emotions in educational games. *Applied Artificial Intelligence*, 16:555–575 (2002)
18. Dautenhahn, K.: Embodiment and interaction in socially intelligent life-like agents. In: *Computation for Metaphors, Analogy and Agent*, ed. by Nehaniv, C.L. (Springer LNAI 1562, 1999), pp. 102–142
19. de Rosis, F., Carolis, B. De, Carofiglio, V.: Shallow and inner forms of emotional intelligence in advisory dialog simulation. In: *Life-like Characters. Tools, Affective Functions and Applications*, ed. by Prendinger, H., Ishizuka, M. (Springer 2003). This volume.
20. de Rosis, F., Carolis, B. De, Pizzulito, S.: Software documentation with animated agents. In: *Proceedings 5th ERCIM Workshop on User Interfaces For All* (1999)
21. Doyle, P.: When is a communicative agent a good idea? In: *Proceedings Agents-99 Workshop on Communicative Agents* (1999)
22. Elliott, C., Brzezinski, J.: Autonomous agents as synthetic characters. *AI Magazine*, 19(2):13–30 (1998)
23. Extempo Systems Inc. URL: www.extempo.com
24. Gratch, J., Rickel, J., André, E., Cassell, J., Petajan, E., Badler, N.: Creating interactive virtual humans: Some assembly required. *IEEE Intelligent Systems*, 54–63 (2002)
25. Harel, D.: Dynamic logic. In D. Gabbay and F. Guenther, editors, *Handbook of Philosophical Logic. II: Extensions of Classical Logic*, pages 497–604. Reidel, Boston, MA, 1984.
26. Hayes-Roth, B.: Adaptive learning guides. In: *Proceedings of the IASTED Conference on Computers and Advanced Technology in Education* (2001)

27. Hayes-Roth, B.: Principles of design for life-like characters. In: *Life-like Characters. Tools, Affective Functions and Applications*, ed. by Prendinger, H., Ishizuka, M. (Springer 2003). This volume.
28. Hayes-Roth, B., Doyle, P.: Animate characters. *Autonomous Agents and Multi-Agent Systems*, 1(2):195–230 (1998)
29. Huang, Z., Eliëns, A., Visser, C.: STEP: A scripting language for embodied agents. In: *Life-like Characters. Tools, Affective Functions and Applications*, ed. by Prendinger, H., Ishizuka, M. (Springer 2003). This volume.
30. Johnson, W.L., Rickel, J., Lester, J.C.: Animated pedagogical agents: Face-to-face interaction in interactive learning environments. In: *International Journal of Artificial Intelligence in Education*, 11:47–78 (2000)
31. Kawamoto, S., Shimodaira, H., Nitta, T., Nishimoto, T., Nakamura, S., Itou, K., Morishima, S., Yotsukura, T., Kai, A., Lee, A., Yamashita, Y., Kobayashi, T., Tokuda, K., Hirose, K., Minematsu, N., Yamada, A., Den, Y., Utsuro, T., Sagayama, S.: Galatea: Open-source software for developing anthropomorphic spoken dialog agents. In: *Life-like Characters. Tools, Affective Functions and Applications*, ed. by Prendinger, H., Ishizuka, M. (Springer 2003). This volume.
32. Kitamura, Y.: Web information integration using multiple character agents. In: *Life-like Characters. Tools, Affective Functions and Applications*, ed. by Prendinger, H., Ishizuka, M. (Springer 2003). This volume.
33. Lester, J.C., Converse, S.A., Kahler, S.E., Barlow, S.T., Stone, B.A., Bhogal, R.S.: The Persona effect: Affective impact of animated pedagogical agents. In: *Proceedings of CHI-97* (ACM Press, New York 1997), pp. 359–366
34. Lisetti, C., Nasoz, F., LeRouge, C., Ozyer, O., Alvarez, K.: Developing multimodal intelligent affective interfaces for tele-home health care. *International Journal of Human-Computer Studies* (2003) To appear.
35. Mariott, A., Beard, S.: gUI: Specifying complete user interaction. In: *Life-like Characters. Tools, Affective Functions and Applications*, ed. by Prendinger, H., Ishizuka, M. (Springer 2003). This volume.
36. Mariott, A., Stallo, J.: VHML—Uncertainties and problems. A discussion. In *Proceedings AAMAS-02 Workshop on Embodied conversational agents—let’s specify and evaluate them!* (2002)
37. Marsella, S., Gratch, J., Rickel, J.: Expressive behaviors for virtual worlds. In: *Life-like Characters. Tools, Affective Functions and Applications*, ed. by Prendinger, H., Ishizuka, M. (Springer 2003). This volume.
38. Mateas, M., Stern, A.: A Behavior Language: Joint action and behavioral idioms. In: *Life-like Characters. Tools, Affective Functions and Applications*, ed. by Prendinger, H., Ishizuka, M. (Springer 2003). This volume.
39. McBreen, H., Shade, P., Jack, M., Wyard, P.: Experimental assessment of the effectiveness of synthetic personae for multi-modal e-retail applications. In: *Proceedings 4th International Conference on Autonomous Agents (Agents’2000)* (ACM Press, New York, 2000), pp. 39–45
40. Microsoft. *Developing for Microsoft Agent*. Microsoft Press (1998)
41. Mori, J., Prendinger, H., Mayer, S., Dohi, H., Ishizuka, M.: Using biosignals to track the effects of a character-based interface. In: *Proceedings UM-03 Workshop on “Assessing and Adapting to User Attitudes and Affect: Why, When and How?”* (2003). To appear.
42. Nishida, T.: Social intelligence design – An overview. In: *New Frontiers in Artificial Intelligence. Joint JSAI 2001 Workshop Post-Proceedings* (Springer 2001), pp. 3–10

43. Paiva, A. (editor): *Affective Interactions. Towards a New Generation of Computer Interfaces*. (Lecture Notes in Artificial Intelligence 1814, Springer Verlag, Berlin Heidelberg New York (2000))
44. Paiva, A., Prada, R., Machado, I., Martinho, C., Vala, M., Silva, A.: Playing with agents - Agents in social and dramatic games. In: *Life-like Characters. Tools, Affective Functions and Applications*, ed. by Prendinger, H., Ishizuka, M. (Springer 2003). This volume.
45. Petta, P.: Lessons from the invisible person for situated life-like character design. In: *Life-like Characters. Tools, Affective Functions and Applications*, ed. by Prendinger, H., Ishizuka, M. (Springer 2003). This volume.
46. Picard, R.W.: *Affective Computing*. (The MIT Press, 1997)
47. Prendinger, H., Descamps, S., Ishizuka, M.: Scripting affective communication with life-like characters in web-based interaction systems. *Applied Artificial Intelligence*, 16(7–8):519–553 (2002)
48. Prendinger, H., Ishizuka, M.: Evolving social relationships with animate characters. In: *Proceedings of the AISB-02 Symposium on Animating Expressive Characters for Social Interactions* (2002), pp. 73–78
49. Prendinger, H., Saeyor, S., Ishizuka, M.: MPML and SCREAM: Scripting the bodies and minds of life-like characters. In: *Life-like Characters. Tools, Affective Functions and Applications*, ed. by Prendinger, H., Ishizuka, M. (Springer 2003). This volume.
50. Reeves, B., Nass, C.: *The Media Equation. How People Treat Computers, Television and New Media Like Real People and Places*. (CSLI Publications, Center for the Study of Language and Information. Cambridge University Press, 1998)
51. Rist, T.: Issues in the design of scripting and representation languages for life-like characters. In: *Life-like Characters. Tools, Affective Functions and Applications*, ed. by Prendinger, H., Ishizuka, M. (Springer 2003). This volume.
52. Rist, T., André, E., Baldes, S., Gebhard, P., Klesen, M., Kipp, M., Rist, P., Schmitt, M.: An evolutionary perspective on embodied presentation agents and their application fields. In: *Life-like Characters. Tools, Affective Functions and Applications*, ed. by Prendinger, H., Ishizuka, M. (Springer 2003). This volume.
53. Rousseau, D., Hayes-Roth, B.: A social-psychological model for synthetic actors. In: *Proceedings 2nd International Conference on Autonomous Agents (Agents-98)* (ACM Press, New York 1998), pp. 165–172
54. Sumi, Y.: Interface agents that facilitate knowledge interactions between community members. In: *Life-like Characters. Tools, Affective Functions and Applications*, ed. by Prendinger, H., Ishizuka, M. (Springer 2003). This volume.
55. Sumi, Y., Mase, K.: Supporting the awareness of shared interests and experiences in communities. *Journal of Human-Computer Studies*, 56(1):127–146 (2002)
56. Takahashi, T., Takeda, H., Katagiri, Y.: Script language for embodied agents as personal conversational media in online communities. In *Proceedings AAMAS-02 Workshop on Embodied Conversational Agents: Let's Specify and Compare Them!* (2002)
57. Tanaka, H., Tokunaga, T., Yusuke, S.: Animated agents capable of understanding natural language and performing actions. In: *Life-like Characters. Tools, Affective Functions and Applications*, ed. by Prendinger, H., Ishizuka, M. (Springer 2003). This volume.

58. Thalmann, D., Noser, H., Huang, Z.: Autonomous virtual actors based on virtual sensors. In: *Creating Personalities for Synthetic Actors*, ed. by Trappl, R., Petta, P. (Springer Verlag, Berlin Heidelberg New York, 1997), pp. 25–42
59. Thomas, F., Johnston, O.: *Disney Animation: The Illusion of Life* (Abbeville Press, New York, 1981)
60. Trappl, R., Petta, P.: *Creating Personalities for Synthetic Actors* (LNAI State-of-the-Art Survey 1195, Springer Verlag, Berlin Heidelberg New York, 1997)
61. Weiser, M.: The computer for the 21st century. *Scientific American*, pages 94–100 (1991)
62. Zoesis Studios. URL: www.zoesis.com/corporate/index.html

Index

- Émile, 8
- ABL (A Behavior Language), 6
- Actors
 - synthetic, 2
- Affect
 - of user, 7
- Affective Computing, 4
- Agents
 - anthropomorphic, 2
 - cartoon-style, 2
 - realistic, 2
 - robotic, 2
- AgentSalon system, 9
- AiA travel agent, 8
- APML (Affective Presentation Markup Language), 6
- Avatar Arena, 8
- Avatars, 2
- BEAT (Behavior Expression Animation Toolkit), 6
- Believability, 2
- CBI (Carmen's Bright IDEAS), 8, 9
- Characters
 - animate, 2
- CML (Character Markup Language), 5
- Creatures, 2
- CrossTalk installation, 8
- Disappearing Computer, 4
- ECAs (Embodied Conversational Agents), 2
- EMOTE system, 6
- Emotions, 2
- Façade, 9
- Galatea software toolkit, 7
- Gestalt User Interface, 7
- HCI (Human-Computer Interaction, 3–5
- Invisible Computing, 4
- Kirai system, 9
- Learning environments, 8
- Life-like Character applications
 - entertainment, 8
 - guidance systems, 9
 - information retrieval, 9
 - medical, 9
 - online communities, 9
 - presentation, 8
 - therapeutic, 9
- Life-like Characters
 - as actors, 7
 - as communication partners, 7
 - as information experts, 8
 - as personal representatives, 7
 - as presenters, 7
 - as sales persona, 7
 - as trainers, 7
 - as tutors, 7
 - at information booths, 7

- in guidance systems, 7
- in learning environments, 7
- in therapy, 7
- MCI (Multiple Character Interface), 9
- MIAU platform, 8
- MPML (Multi-modal Presentation Markup Language), 6, 8
- MRE (Mission Rehearsal Exercise), 8
- NLU (Natural Language Understanding), 9
- Non-player Characters, 2
- PAR (Parameterized Action Representation), 6
- Personal Effect, 3
- Personality, 2
- PPP Persona, 8
- Recommendation Battlers, 9
- Relational Agents, 4
- RoboCup commentator system, 8
- SCREAM (Scripting Emotion-based Agent Minds), 7, 8
- Scripting
 - high level, 5
 - low level, 5
- Social Actors, 3, 4
- Social Computing, 3–5
- Social Intelligence, 2
- Social Intelligence Design, 5
- Social Interfaces, 3
- STEP (Scripting Technology for Embodied Persona), 5
- STEVE architecture, 8
- Ubiquitous Computing, 4
- Venus and Mars, 9
- VHML (Virtual Human Markup Language), 5